

GC PROPLS

PLATE HEAT EXCHANGER FRAME

Improved Entrance Area

"Building the best, servicing the rest"...



QUALITY

- Skillfully crafted to 3A sanitary standards.
- Operating pressures up to 200 psig [14 bar].
- Made in the USA.

DEPENDABILITY

- Stainless steel clad design polished to a consistent #4 finish.
- Oversized tie bolts for easy open/close operation.
- Built for full wash-down environment.

RELIABILITY

- Heavy 14 gauge stainless steel clad material for long life.
- Strong internal solid steel plate rugged and proven design.
- •Enclosed tie bolt bearings.

EXPANDABILITY


- Frames supplied for plate expandability.
- All eight ports supplied as standard for future duty expansions.
- Terminals available to safely separate heating, cooling or regeneration sections.


PLATES

- Pro2 plates measure 331/4" x 117/8" [855 x 302 mm] - Made in the USA.
- Made of a heavy 0.7mm thick, 316 stainless steel with a high quality sanitary finish.
- Features an improved heat transfer pattern and a wide gap to resist fouling.
- Line-contact support points to increase the life of the plate.
- Increased entrance area crosssection to decrease pressure loss.
- Solid metal-to-metal contact to allow high operational pressures.




PRO2-SH







This drawing is the confidential property of AGC HEAT TRANSFER and it must not be reproduced in any form without written consent



GENERAL INFORMATION			
Plate and Gasket Weight:	3.5 lbs 316 S.S. / 1.58 kg 1.9 lbs Titanium / 0.86 kg		
Plate Capacity:	0.16 US Gallons / 0.61 I		
Heat Transfer Area:	1.87 ft² / 0.17 m²		
Plate Thickness:	0.7 mm		
Frame Weight: (according to size)	803-980 lbs / 364-445 kg		
Standard Frame Connections:	21/2" Sanitary Clamp		
Terminal Connections:	2" Sanitary Clamp		
Terminal Weight:	130 lbs / 59 kg		

FRAME SIZE	BALL FOOT CENTERS [L]	RAIL LENGTH [A]	PLATE CAPACITY
2	25 ⁷ /8" [657]	24" [610]	50
3	37 ⁷ /8" [962]	36" [915]	100
4	49 ⁷ /8" [1267]	48" [1219]	150
5	61 ⁷ /8" [1572]	60" [1524]	200
6	73 ⁷ /8" [1876]	72" [1829]	250

Dimensions not to be used for construction



Western

9109 SE 64th Ave. Portland, OR 97206 503.774.7342 800.715.8820 FAX 503.774.2550

Central

1325 Remington Rd. Suite T Schaumburg, IL 60173 847.301.6890 FAX 503.774.2550

Eastern

10129 Piper Lane Bristow, VA 20136 703.257.1660 800.825.8820 FAX 703.330.7940



