

Haynes Manufacturing Company

1. Product and Company Identification

Product Name: Haynes CIP FILM

Chemical Name: N/A

Chemical Family: Petroleum Lubricant

Manufacturer: Haynes Manufacturing Co.

24142 Detroit Road

Westlake, Ohio 44145, USA

Emergency Telephone Number: 1-800-992-2166

1-440-871-2188

For MSDS, Product Safety, or Regulatory Inquiries call: 1-440-871-2188 or

1-440-871-2188

Customer Service: 1-800-992-2166 or 1-440-871-2188

2. Hazards Identification

GHS Classification: Not classified as dangerous under EC/GHS-

criteria

Human Health Hazards: None

Physico-chemical and environmental hazards and effects: None

HMIS RATING USA

Health: 0
Flammability: 1
Reactivity: 0
PPI: -

3. Composition / Information of Ingredients

The composition of this product is proprietary.

This product does not contain hazardous ingredients.

4. First Aid Measures

Swallowing

WHEN MOLTEN ONLY (molten product can cause thermal burns). Obtain medical attention immediately. This is not a toxic substance.

Inhalation

No emergency care anticipated. WHEN MOLTEN ONLY (molten product can cause thermal burns). Obtain medical attention immediately.

Revision Date: 01/29/14 Page 1 of 7



Haynes Manufacturing Company

Skin

WHEN MOLTEN ONLY (molten product can cause thermal burns) – In serious cases, use emergency shower immediately. Immediately flush skin thoroughly with water for at least 15 minutes while removing contaminated clothing and shoes. Obtain medical attention.

Eye Contact

WHEN MOLTEN ONLY (molten product can cause thermal burns) – Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention.

5. Fire Fighting Measures

Flash Point: > 93.4°C (200°F) PMCC, ASTM D93

NFPA CLASSIFICATION USA

Health: 0
Flammability: 1
Reactivity: 0
Special Provisions: -

Extinguishing media

Suitable: Treat as an oil fire:

- dry chemical

- carbon dioxide (in case of small fires)

water fogfoam

Unsuitable: Do not use water jet. Oil will float on water and can spread

any fire.

Special fire fighting procedures:

Do not direct a solid stream of water or foam into burning material; this may cause spattering and spread the fire. If a rail or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

Revision Date: 01/29/14 Page 2 of 7



Haynes Manufacturing Company

Special protective equipment for firefighters

Self-contained breathing apparatus.

Unusual fire and explosion hazards

Following products may be produced during a fire: Oxides of carbon.

6. Accidental Release Measures

Personal Precautions

Wear suitable protective equipment.

Environmental Precautions

Avoid runoff to sewers or waterways. Dike area of spill to prevent spreading and pump liquid to salvage tank. Waste: avoid washing into watercourses. Use methods consistent with local regulations or incinerate.

Methods for Cleaning Up

Dike to contain spill. Absorb on inert material such as sand, earth, vermiculite. After cooling, scrape and/or shovel material. Stop the leak if it can be done without risk. Floor may be slippery; use care to avoid falling.

7. Handling and Storage

HANDLING

Do not handle at temperatures >+40°C, unless wearing appropriate protective equipment.

Ventilation

General (mechanical) room ventilation is expected to be satisfactory for use at room temperature.

STORAGE

Storage requirements

Keep away from heat, sparks and flame. Do not store at temperatures: >+40°C without proper safety review of storage equipment. Store protected from light.

8. Exposure Controls / Personal Protection

Revision Date: 01/29/14 Page 3 of 7



Haynes Manufacturing Company

EXPOSURE LIMIT VALUES

No exposure limits have been established.

OCCUPATIONAL EXPOSURE CONTROLS

Respiratory protection

None expected to be needed.

Hand protection/protective gloves

Wear oil resistant gloves. WHEN MOLTEN ONLY: wear gloves impervious to this material.

Eye protection

WHEN MOLTEN ONLY: Face shield or chemical splash goggles in case of splashing.

Skin protection

WHEN MOLTEN ONLY: Wear protective clothing, such as long sleeves to minimize skin contact.

Environmental Exposure Controls:

None expected to be needed.

9. Physical and Chemical Properties

Appearance

Physical State: Semi-solid.

Color: White to light yellow.
Odor: None or Mild Petroleum.

Odor Threshold: N/A

Important health, safety and environmental information

Flash Point: >93.4°C (200°F) Method: PMCC,

ASTM D93

Upper explosion limits:

Lower explosion limits:

Vapor Pressure:

Not determined

Not determined

Not determined

Not determined

Not determined

Density: $0.75 - 0.87 \text{ g/cm}^3 \text{ at } 100^{\circ}\text{C}$

Bulk Density:
Solubility in Water:
Solubility in organic solvents:
Not available
Insoluble
Soluble

Revision Date: 01/29/14 Page 4 of 7



Haynes Manufacturing Company

Kinematic viscosity: 5 – 30 mm²/s at 100°C

Boiling Point: >230°C
PH: N/A
Specific gravity (H2O=1) <1

Partitioning coefficient: log POW: >6 This product is soluble in

oil.

Vapor Density: N/A
Percent volatiles: Nil

Autoignition Temperature: No data Melting Point: 35 - 80°C

10. Stability and Reactivity

Stability: Stable

Conditions/Materials to avoid: Extreme temperature and direct

sunlight/ultraviolet light and strong

oxidizing agents.

Hazardous combustion products

Burning can produce the following combustion products: Oxides of carbon and Soot.

Hazardous polymerization: Will not occur.

11. Toxicological Information

GENERAL

No evidence of harmful effects from available information.

12. Ecological Information

This product is stable in water, and can be mechanically separated from water. The water may be suitable for disposal in a biological waste water treatment plant.

13. Disposal Considerations

Dispose of in accordance with appropriate Federal, State and local regulations or incinerate.

Revision Date: 01/29/14 Page 5 of 7



Haynes Manufacturing Company

14. Transport Information

ADR/RID

(when transported at <100°C) This product is not regulated by ADR.

When transported above >100°C – UN3257 ELEVATED TEMPERATURE LIQUIDS, N.O.S. (9), III, Class: 9 (M9), UN No.: 3257, Packaging Group: III, Hazard No.: 99, Label: 9, Technical Description: Petroleum Lubricant

Freight Description Road: 65 Petroleum Oil, N.O.I.B.N.

IMDG/ICAO

This product is not regulated by IMDG/ICAO.

TDG-CANADA

This product is not regulated by TDG.

15. Regulatory Information

EC/GHS classification

According to EC/GHS regulations this product is not classified or labeled

New Jersey Worker and Community Right-To-Know Act (Labeling Requirents)

Chemical Name CAS# New Jersey TS Number

Petroleum Lubricant 8009-03-8

EPA Hazard Categories (SARA 311, 312): None

WHMIS Classification: This product is not a WHMIS controlled product.

CHEMICAL INVENTORY

<u>Canada:</u> The ingredients of this product are on the DSL.

Europe: The ingredients of this product are on the

EINECS inventory.

United States: The ingredients of this product are on the

TSCA inventory.

Australia: The ingredients of this product are on the AICS

inventory.

Japan: The ingredients of this product are on the

ENCS inventory.

Revision Date: 01/29/14 Page 6 of 7



Haynes Manufacturing Company

16. Other Information

Recommended uses and restrictions

Please consult the product and/or application information bulletins for this product.

Further information, Europe

Where appropriate, use CE approved personal protection equipment.

This Safety Data Sheet conforms to EC Directed 1907/2006 and amendments.

Prepared By:

Haynes Manufacturing Company 24142 Detroit Road Westlake, Ohio 44145

We believe the statements, technical information, and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, expressed or implied, and we assume no responsibility for any loss, damage, of expense, direct or consequential, arising out of their use.

Revision Date: 01/29/14 Page 7 of 7